



**COSENTINO**  
imagine & anticipate

## **DECLARATION OF PERFORMANCE**

### **Nº 092013DK**

**1. Name and identification code:**

Product: Dekton®, Dekton® Xgloss and Dekton®  
Grip+

Code: Family I – II – III - IV

**Family I** Aldem, Ananké, Borea, Bromo, Domoos, Fossil, Galema, Kadum, Kelya, Keon, Keranium, Kira, Korus, Kreta, Laos, Milar, Odin, Orix, Sirius, Sirocco, Soke, Strato, Valterra, Vegha, Ventus, Vera. - XGLOSS: Spectra, Lumina, Blaze, Splendor, Manhattan

**Family II:** Ariane, Aura, Aura 15, Entzo, Kairos, Lunar, Nayla, Nilium, Opera, Zenith.  
- XGLOSS: Halo, Fiord, Tundra, Glacier, Natura, Natura 18, Vienna

**Family III:** Aged Timber, Bento, Blanc Concrete, Danae, Dove, Edora, Gada, Irok, Makai, Sarey, Sterling. XGLOSS: Qatar

**Family IV:** Trilium, Radium

**2. Name and address of manufacturer:**

Company: Cosentino S.A

Address: Carretera A-334, km 59, código postal 04850 Cantoria (Almería) - Spain

# STANDARD EN 14411:2012

**Product:** Ultracompact surfaces.

**Prior Use:** For internal or external walls and flooring, including stairs, in buildings and industrial facilities.

Assessment and verification system of the constancy of performance: 4

**Conformity:** Conforms the annex ZA of the standard EN 14411.

Essential Characteristics	Performance	Harmonised technical specifications
Fire reaction	A1, A1 <sub>FL</sub>	Non test (See Directive 96/603/EC and their modifications)
Release of dangerous substances		EN ISO 10545-15
Cadmium	< 0.02 mg/l *1	
Lead	< 0.2 mg/l *1	
Breaking strength		EN ISO 10545-4
Family 1	14966 N	
Family 2	13359 N	
Family 3	13818 N	
Family 4	15620 N	
<b>Slipperiness</b>		
Smooth Matt		
Aura, Aura 15, Danae, Domoos, Entzo, Fossil, Galema, Irok, Kadum, Kairos, Kelya, Keon, Keranium, Korus, Milar, Nayla, Nilium, Oriz, Radium, Sarey, Sirocco, Sterling, Strato, Trilium, Vegha, Ventus, Zenith.	48 USRV dry 23 USRV wet	CEN/TS 16165 (EN 14231)
	49 USRV dry 22 USRV wet	CEN/TS 16165 (EN 14231)
Textured   Slate-like/limestone Sirius, Gada, Edora, Valterra, Dove, Blanc Concrete.		CEN/TS 16165 (EN 14231)
Textured   Wood-like Ananké, Borea, Aldem, Odin, Ariane, Bento, Makai, Aged Timber	44 USRV dry 21 USRV wet	
Polish (Xgloss)		
Spectra, Lumina, Blaze, Splendor, Halo, Fiord, Tundra, Glacier, Manhattan, Natura, Natura 18, Qatar, Vienna	103 PSRV dry 10 PSRV wet	CEN/TS 16165 (EN 14231)
Velvet Finish Opera, Portum	*2	CEN/TS 16165 (EN 14231)
<b>Slipperiness - Dekton® Grip+</b>		
Dekton Grip+	R11	DIN 51130
Keon, Kira, Kreta, Laos, Orix, Soke, Strato, Trilium, Vera	C	DIN 51097
	45	CEN/TS 16165 (ENV 12633)
	≥ 0.69	ANSI A137.1 (DCOF)
<b>Durability</b>		
Internal use	Pass	
External use (frost resistance)	Pass	EN ISO 10545-12
Tactility	NPD	CEN/TS 15209

\*1 Values below the limit of quantification.

\*2 Pending test.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed by and in representation of the manufacturer by:

**Miguel Segovia**



Updated: January 2019

PLACE AND DATE OF ISSUE:

Cantoria, 01/2019

