

Declaration of Performance CE

N - 092023CEUK

UKIYO
PATTERNS GV2 - GV3

All the data collected in this document are based on tests carried out in independent external laboratories.

Name and address of manufacturer

Company: Cosentino Industrial, S.A.U.

Address: Carretera A-334, km 59, 04850 Cantoria (Almeria) - Spain

**TECHNICAL
CONTENT**

EN 14411:2012

Product: Ultracompact surface unglazed dry pressed, rectified and with water absorption $\leq 0.5\%$.
Prior use: For internal or external walls and flooring, including stairs, in buildings and industrial facilities.
Assessment and verification system of the constancy of performance: 4.
Conformity: Conforms the Annex G of the standard EN 14411:2012.

Essential characteristics	Performance	
	Pattern GV2	Pattern GV3
Water absorption EN 10545-3	0.1%	
Flexural strength ⁽¹⁾ EN 10545-4		
Parallel groove to the load axis	36.2 MPa	26.1 MPa
Perpendicular groove to the load axis	42.9 MPa	41.3 MPa
Resistance to thermal shock EN 10545-9	Not recommended for use in outdoor areas with high temperature variations	
Durability EN ISO 10545-12		
Internal use	Pass	
External use (Frost resistance)	Pass	
Release of dangerous substances EN ISO 10545-15		
Cadmium	< 0.02 mg/l	
Lead	< 0.2 mg/l	
Adhesion ⁽²⁾ EN 12004	1.94 N/mm ²	
Fire reaction EN 13501-1	A1, A1fl	

→ (1) Average flexural values. (2) The breakage was caused by the adhesive and not by Dekton®.

The performance of the product identified above is in conformity with the set of declared performance/s. This *Declaration of Performance* is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed by and in representation of the manufacturer by:


Valentín Tijeras
VP Global Product, R&D and Quality

Place and date of issue:
Cantoria, 11/2023